

EZ Lift Manual Chain Hoists

Authorized Sales & Service
J. HERBERT CORPORATION
 Call 1-800-255-0588
 407-846-0588 Fax: 846-1066
 info@jherbertcorp.com

Visit us online:
www.jherbertcorp.com

RM Series II Manual Chain Hoist



- 10 ft (3 m) standard lift. Hand chain is 2 ft (0.5 m) less than lift. Additional lifts available.
- Overload limiting device to prevent lifting loads beyond rated capacity. (Except 1/4 ton [250 kg] unit).
- High strength, grade 80 alloy steel load chain with galvanized finish for corrosion resistance.
- Hooks are alloy steel, heat treated and equipped with hook latches and inspection points.
- Dual pawl Weston-style brake with two brake friction discs provides four braking surfaces.
- Meets or exceeds international standards, including ASME B30.16.



Model	Capacity Ton [kg]	Falls	Chain Pull ¹ Lbs. [N]	Overhaul Ratio ²	Headroom Inch [mm]	Weight ** Lbs. [kg]
RMII-250	1/4 [250]	1	53 [235]	17	11 [280]	14 [6.4]
RMII-500	1/2 [500]	1	54 [240]	33	13.6 [345]	25 [11.3]
RMII-1000	1 [1000]	1	57 [250]	53	14.8 [376]	29 [13]
RMII-1500	1.5 [1500]	1	60 [265]	78	17.4 [442]	40 [17.8]
RMII-2000	2 [2000]	1	76 [335]	90	18.5 [470]	45 [20.2]
RMII-3000	3 [3000]	1	84 [372]	106	21.6 [548]	78 [35]
RMII-5000	5 [5000]	2	81 [360]	197	27.1 [688]	91 [41.3]
RMII-7500	7.5 [7500]	3	84 [372]	296	27.1 [688]	137 [62]
RMII-10000	10 [10,000]	4	84 [372]	394	30.1 [765]	173 [78.5]

Note: Reference Technical Guide for additional dimensional data

¹ Effort required to lift rated load.

² Ft [m] of hand chain movement required for 1ft [m] of lift.

** Note: Weights shown are for models with 10 ft. (3m) of lift