



# R&M Spacemaster® EX Hazardous Location Electric Wire Rope Hoists

[www.rmhoist.com](http://www.rmhoist.com)






# R&M Spacemaster® EX Hazardous Location Electric Wire Rope Hoists

R&M Materials Handling, Inc.  
4501 Gateway Blvd.  
Springfield, Ohio 45505  
Phone: (937) 328-5100  
Fax: (937) 325-5319  
Nationwide Toll Free:  
1-800-955-9967  
[www.rmhoist.com](http://www.rmhoist.com)

Bulletin No.: EX-05

The Spacemaster® EX is the hazardous location version of the industry leading Spacemaster® SX hoist. An innovative design that includes a large drum diameter gives the Spacemaster® EX hoists the lowest headrooms and best wheel loads in the industry, while providing near true vertical lift with single reeving, as well as exceptional hook approaches and heights of lift.



### Standard Configurations:

- Foot mount, low headroom, normal headroom and double girder
- 1-1/2—20 ton [1600—20,000 kg] capacities
- Lifts starting at 13ft [4m] to 324ft [99m] and beyond
- Lift speeds 10/1.5—62/10 fpm [3/0.5—19/3 m/min.]
- 460, 575/3/60 or 380/3/50 supply
- ASME H3 or ASME H4 duty [FEM 1Am, 2m, or 3m] ratings
- For Class I group C & D Division 2 Applications
- Temperature classification is T3
- Single reeved or double reeved

### Standard Features:

- Two speed hoist with 6:1 ratio, contactor control
- Hoist motor is class F insulated, 60% effective duty and thermally protected
- Low maintenance, sealed hoist brake
- Two speed trolley with 4:1 ratio, contactor control
- Electro-mechanical load limit switch
- 2-position hoist limit switch
- IP55/NEMA 4 rated control panel
- CSA C/US approved
- Approx. 40:1 drum to rope diameter ratio for extended rope life
- Rope guide with spring loaded pressure roller
- Trolley motor with compact disc brake
- Trolley bumpers
- Mainline contactor
- 115 Volt control transformer
- Push-button assembly & pendant
- Available options: bronze coated load hook; bronze trolley wheels



### YOUR DISTRIBUTOR CONTACT IS:

*Authorized Sales & Service*  
**J. HERBERT CORPORATION**  
 Call 1-800-255-0588  
 407-846-0588 Fax: 846-1066  
 info@jherbertcorp.com  
 Visit us online:  
[www.jherbertcorp.com](http://www.jherbertcorp.com)